

5.6 corner wall
curb 23.5
Section 26

Town 7 Range 5

STONE

corner of
concrete
wall

side
WALK 5' -> 6.5 brick
picks

31.4
REGAL
STORE

STONE

January 9 1950

I commenced a Survey of Section 26, T. 7, R. 5
for J. R. Williams

CORNER ESTABLISHED.	Monument.	Device.	WITNESS POINTS OR BEARING TREES.	Mark or Dia. in Inches.	COURSE.	Links Distant.	REMARKS.
N.W. N.W.	STONE		S W of concrete wall corner	53.9 ft			
S.W. S.W.	STONE		N W corner wall north to curb	23.5 "			
				5.6 - "			

} C. B.

NW $\frac{1}{4}$ NW $\frac{1}{4}$ NW $\frac{1}{4}$ corner

Lee Richardson
Surveyor Greene County.

Var.

Course.	Point of Beginning.	Chains Distance.	Corrected Bearings.
NW corner of Sec. - 26	RUN SEC-LINE to SW. SW.		
of sec. - 26 found stone			
Established N.W. corner of N.W. - N.W.			

N $\frac{1}{4}$ corner

black
locust
stake

12" nail in B. Locust 15" N28°46' 79.8'

Nail in B. Locust 15" N25°20' E. 78'